







Use ambient air to heat your pool



Energy efficient heating

A swimming pool is a major financial investment. Getting the most out of your pool, means keeping the pool at a swimmable temperature for the maximum number of hours in each day and the maximum number of days in each year. A pool heat pump will economically keep your pool warm 24 hours a day.

Compared to gas and electric heaters, the Electroheat MKV pool heat pump range use just a fraction of the energy to generate the same amount of heat and unlike solar heating; there is no reliance on the sun as the latent heat in the air is used.

For every 1kW of electricity consumed, Electroheat can produce up to 6kW of heat.





Unique modern robust design - noise & vibration reduction



Hydrophilic Blue fin evaporator technology

- improved corrosion resistance



Improved condensate collection -

two fitted spigots to allow drainage hose connection



Refrigerant pressure gauge -

confirmation of refrigerant gas charge



smart controls for temperature management and self diagnosis



INBUILT SAFETY DEVICES for water flow, refrigerant level and compressor startup delay



POWERFUL HEAT TRANSFER through the coiled heat exchanger maximising water contact



DUAL COIL TITANIUM Heat Exchanger is highly resistant to ozone, iodine, baquacil, salt and chlorinated water



SCROLL COMPRESSOR for improved efficiency and high performance







R410A REFRIGERANT, ozone friendly and maximises performance



LARGE EVAPORATOR **AREA** to extract more ambient heat



Warranty - Residential 10 years - titanium heat exchanger 3 years - compressor 2 years - all other components 1 year - labour

Warranty- Commercial - 1 year

Conditions apply, see the Waterco Limited warranty set out in the Waterco Warranty Booklet or view it at www.waterco.com



Electroheat MKV pool heat pumps feature compact design and horizontal venting and are ideal for heating:

✓ Available in 9, 12, 15, 19 & 23kW heating capacities

The Electroheat heat pump range are an ideal solution for heating:



Swimming pools to extend the season



Swimming pools for year round enjoyment



Plunge pools



Swim spas and spas

Extend the swimming season

Energy efficient way to heat your pool



Frequently asked questions

SHOULD I USE A POOL COVER?

The most effective way to prevent heat loss is to install a pool cover. An un-blanketed pool loses 2-3 times more heat than a blanketed pool. Pool covers virtually eliminate evaporation and reduce heat loss by insulating the surface of the pool, greatly reducing pool heating costs. As with all pool heaters, it would be advisable to use a pool cover at night, and when the pool is not in use.

WHAT IS THE MINIMUM AMBIENT OPERATING **TEMPERATURE?**

The heat pump will actually operate down to an ambient air temperature of 10°C, but with minimal heat output. Therefore we recommend that the minimum operating temperature should be 10°C.

WHAT IS THE BEST LOCATION FOR THE **ELECTROHEAT?**

The location of the Electroheat is very important in keeping installation costs to a minimum, while providing for maximum efficiency of operation as well as allowing adequate service and maintenance access.

The unit should be located as close as practically possible to the existing pool pump and filter to minimise water piping. The use of 90 degree bends and short radius elbows in the water piping should be kept to a minimum. The longer the distance from the pool, the higher the heat loss from the piping.

CAN THE ELECTROHEAT BE ENCLOSED?

The Electroheat is designed for outdoor installation and should not be installed in totally enclosed areas such as a shed, garage, etc., unless mechanical ventilation is provided to ensure adequate air exchange for proper operation. Re-circulation of cold discharged air back into the evaporator coil will greatly reduce unit's heating capacity and efficiency.

WHAT IS THE ELECTROHEAT'S PERFORMANCE **DEPENDENT ON?**

Performance will fluctuate depending on water and weather temperatures. 5 important factors determine the performance of Electroheat:

- 1. Size of the pool
- 2. The desired temperature of the pool
- 3. Ambient air temperature the warmer the air, the better the performance
- 4. The presence of a pool cover
- 5. The size of the heater

WHAT IS THE ELECTROHEAT'S HEATER RUNNING TIME?

Most units should be sized to operate during the pool filtering cycle time of 8 - 12 hours daily, providing a steady flow of heated water. On warmer days the heater will run less because the heat loss will be less.

Electroheat heat pumps have a lower heating capacity on a BTU/hr basis compared to fossil fuel based pool heaters such as gas heaters. Therefore, Electroheat heat pumps require longer operation to accomplish the desired temperature.

Between 10°C to 18°C, it will increase your water temperature by 3°C to 5.5°C a day. Over 21°C you should obtain an increase up to 0.8°C a hour and over 26°C up to 1.1°C an hour depending on the size of the pool, the size of the heat pump, the water temperature, and the ambient air temperature at the moment of operation.

Even though the Electroheat may require longer operation, it will still heat the pool far more economically.

HOW DOES ELECTROHEAT COMPARE WITH SOLAR **HEATING AND GAS HEATING?**

Solar

- Fuelled by the power of the sun, solar heating systems are a low-cost method of heating up your pool water.
- As solar heating is reliant on the sun, they are best used to extend the swimming season.
- Virtually no operating costs, just the cost of electricity to pump the pool water through the solar absorber on the roof.

Gas heaters

- · Gas heaters are the fastest method for heating your pool, providing a comfortable temperature for swimming on demand. Gas is best for heating pools or spas for short periods of time.
- Gas heaters can easily maintain any desired temperature regardless of the weather.
- Gas heaters are effective, but expensive to operate.

Heat pumps

- Heat pumps may not heat up the swimming pool as fast as gas heaters, but are more energy efficient.
- Heat pumps require a small amount of electricity; its heat energy source is extracted from the ambient air.

Performance Specifications									
	Electroheat MKV								
Nominal Power Output (kW)*	9	12	15	19	23				
Nominal Heating Capacity BTU*	30700	41000	51000	64000	78,500				
Product Code	278095	278123	278152	278192	278232				
Power Output (kW): Air 26C / Water 26C / RH63%	8.9	11.7	13.5	18.5	21.8				
COP	5.9	6.1	6.1	6.3	6.2				
Power Output (kW): Air 15C / Water 24C / RH 70%	6.8	9.2	9.4	17.0	20.0				
COP	4.8	4.8	4.3	5.8	5.7				
Supply Voltage (VAC)	240	240	240	240	240				
Supply Voltage Phase	Single Phase								
Power Consumption (kW/h)	1.5	1.9	2.2	2.9	3.5				
Full Load Amps	9	12	12	22	30				
Minimum Breaker or Fuse (AMP)	16	20	20	30	40				
Electrical Connection	10A plug	15A plug Terminals							
Min. / Max. Ambient Air Temperature (C)	10 / 40								
Min. / Max. water inlet temp (C)	18 / 40								
Water Connections (mm)	40mm								
Bypass	External 3 x 2 way								
Min. / Max. Water Flow Rate LPM	120 - 230								
Unit Dry Weight (kg)	51 55 79								
Dimensions W x L x H (mm)	1269 x 361 x 717								
Refrigerant	R410A								
Heat Exchanger Max. pressure	3.5 bar / 350 kPa								

Related products:

Electroheat Pro range - Pool heat pumps for commercial applications. Electroheat ECO V range - Pool Heat pumps with inverter technology.

Sizing Chart to Heat Your Pool to 28°C FROM SEPT TO APRIL								
		Temperate Location *		Warm Location **				
		Up to 10 hrs /	o 10 hrs / Day Run time		Day Run time			
Pool Size (m)	Litres	with Pool Cover	No Pool Cover	with Pool Cover	No Pool Cover			
3 x 6	Up to 23000	9kW	15kW	9kW	9kW			
3 x 7	Up to 27000	9kW	15kW	9kW	9kW			
4 x 7	Up to 35000	12kW	23KW	9kW	15kW			
4.5 x 8.5	Up to 50000	15kW	31kW	9kW	19kW			
5 x 10	Up to 65000	19kW	23kW x 2	12kW	23kW			
5.5 x 11	Up to 80000	23kW	23kW x 2	15kW	15kW x 2			
6 x 12	Up to 100000	15kW x 2	23kW x 3	19kW	19kW x 2			

Note: Size and performance are influenced by ambient temperature, humidity, use of a pool cover, night time temperature, pool location, wind factor, water features and if the unit is switched off over night. The recommended sizing in the table above is based on operating the unit up to 10 daytime hours with the pool subjected to normal suburban wind. No allowance has been made for the cooling effects of water features, negative edges or high wind areas. Therefore, any under sizing of the heater for your pool heating requirements is not the responsibility of Waterco.

^{*} Temperate Location (Sydney): - Where minimum average daytime temperatures between September to April are not less than 18°C.

** Warm Location (Brisbane): - Where minimum average daytime temperatures between September to April are not less than 24°C

^{***} Pool heating between May and August will require a larger heat pump. Consult www.watercocalculator.com or contact your local Waterco office.

Clearance



Dimensions





OFFICES - AUSTRALIA

NSW - Sydney (Head Office)

Tel: +61 2 9898 8600

QLD - Brisbane

Tel: +61 7 3299 9900

VIC/TAS - Melbourne

Tel: +61 3 9764 1211

WA - Perth

Tel: +61 8 9273 1900

SA/NT - Adelaide

Tel: +61 8 8244 6000

ACT Distribution Tel: +61 2 6280 6476

OFFICES - OVERSEAS

Waterco (Europe) Limited

Sittingbourne, Kent. UK Tel: +44 (0) 1795 521 733

Waterco (USA) Inc

Augusta, Georgia, USA Tel: +1 706 793 7291

Waterco Canada Boucherville, Quebec, Canada Tel: +1 450 748 1421

Waterco (NZ) Limited

Auckland, New Zealand Tel: +64 9 525 7570

Waterco (C) Limited

Guangzhou, China Tel: +86 20 3222 2180

PT Waterco Indonesia

Jakarta, Indonesia Tel: +62 21 4585 1481

Waterco Singapore Intl Pte Ltd

Nehsons Building, Singapore Tel: +65 6344 2378

Waterco (Far East) Sdn Bhd

Selangor, Malaysia Tel: +60 3 6145 6000

Distributed by:





